

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A combination of a door for closing a cooking compartment of a cooking appliance, and a mobile plate rack for use with the cooking appliance, the combination comprising: with and without
a mobile plate rack which is adapted to be inserted in the cooking appliance and having comprising a mobile plate rack bar and a sealing plate, the sealing plate for sealing [[the]] an opening of the cooking compartment opening in the in a region of [[a]] the mobile plate rack bar when the mobile plate rack is inserted in the cooking appliance, wherein the; and
a door is provided with a captively mounted replacement sealing plate, which is movable between a rest position and an operating position in which it serves as a replacement for the sealing plate of the mobile plate rack when the mobile plate rack is not inserted in the cooking appliance.
2. (Currently Amended) The door combination as claimed in claim 1, wherein the replacement sealing plate is displaceable.
3. (Currently Amended) The door combination as claimed in claim 2, wherein the door further comprises an outer door frame, and wherein the replacement sealing plate, in the rest position, is arranged parallel and adjacent to the outer door frame.

4. (Withdrawn-Currently Amended) The door combination as claimed in claim 2, wherein the replacement sealing plate is laterally guided via two slideways on each side thereof.

5. (Currently Amended) The door combination as claimed in claim 1, wherein the replacement sealing plate is pivotable.

6. (Currently Amended) The door combination as claimed in claim 5, wherein the replacement sealing plate is pivotable by at least 180 degrees.

7. (Currently Amended) The door combination as claimed in claim 5, wherein the door further comprises an outer door frame, and wherein the replacement sealing plate, in the rest position, is arranged parallel and adjacent to the outer door frame.

8. (Currently Amended) The door combination as claimed in claim 5, wherein the replacement sealing plate is pivotable by two pivot bearings on each side thereof.

9. (Currently Amended) The doors combination as claimed in claim 8, wherein the two pivot bearings on each side are vertically spaced from each other.

10. (Withdrawn-Currently Amended) The door combination as claimed in claim 5, wherein the door further comprises an openable inner pane and an outer

pane and the replacement sealing plate, in the rest position, is arranged between the inner and the outer pane.

11. (Withdrawn-Currently Amended) The door combination as claimed in claim 10, wherein the replacement sealing plate is pivotable about a horizontal rotation axis.

12. (Withdrawn-Currently Amended) The door combination as claimed in claim 11, wherein the rotation axis extends beneath the inner pane.